

**FLUORESCENT SOCKETS**

**Medium Bi-Pin Butt-On**

- A. L395W** (white)
- B. L395-2W** (white) with two 4-32 trapped holes


660W-600V, (2) 1/8" dia. mounting holes, rapid-start lampholder with 6" leads



**Single Pin Slimline**

- A. L466** - (660W-1000V)
- B. L467** - (660W-600V)


Dim. 2-21/64"Ht. x 1-29/64" W



**Snap-In Quickwire Slimline**

- A. L516**
- B. L517**


suggested panel opening 1.520", 660W-600V



**Shallow Base Slide On**  
(660W-1000V)

- A. L2537**
- B. L2536**

designed for 20ga. panel mount



**Slide-On Self-Aligning for U-Shape Lamps**

- L13080-U** (standard)


660W-600V, 18-20ga. panel mount



**Safety Tube Locks**  
white plastic reusable

**T199**

locks fluorescent Bi-Pin, Tubes in place for added safety and longer tube life



**Medium Bi-Pin for U-Shape Lamps**

- L13080** (standard)

660W-600V, Dim. 1-1/8" Ht.x 1-3/16" W



**Medium Bi-Pin Shunted**  
For Electronic Ballasts

**L23351**

low profile 18 & 20 ga., 660W-600V



**Circline Connector**

four leads (black, white, blue, red)

**L408**

660W-600V



**Medium Bi-Pin**  
**L3901W**

Dim. 1-55/64" Ht x 1-7/16" W, flush or suurface mounting 660W-600V



**Medium Bi-Pin**


- A. L13351-U** -18 & 20 ga. panel
- B. L13051-UN** - 20 ga. with nut
- C.L13053-UN** - 18 ga. with nut

low profile, 660W-600V, Dim. 1-43/64", Ht.x1-11/64" W.



**Miniature Bi-Pin for T5 Lamp**  
75W-250V **10" leads**

- A. L420**
- B. L420B** (bracket)



**Medium Bi-Pin Standard**

- A. L13357-U** -18 ga. panel
- B. L13357-UN** - captive nut
- C.L13355-U** - 20 ga. panel mount


660W-600V, Dim. 2-33/64", Ht.x1-3/8" W. **T8 & T12**



**Miniature Bi-Pin Snap-In Quickwire**

- A. L13518** - (spring loaded)
- B. L13519** - (fixed end)

suggested panel opening 1.520", 660W-600V



Note: 4 Push in Terminals in back for wires ↑

USA & CANADA

1-800-445-6611

FAX: 1-800-445-6690

[www.MillerLightingProducts.com](http://www.MillerLightingProducts.com)



PHOENIX, AZ

Phone: 602-268-0001

Fax: 602-268-0130

[customerservice@millerlightingproducts.com](mailto:customerservice@millerlightingproducts.com)